


GENERAL NOTES:

- FOR GROUPS OF TREES PLACE BARRICADES BETWEEN TREES AND CONSTRUCTION ACTIVITY AT THE EDGE OF THE TREES CRITICAL ROOT ZONE.
- TREE PROTECTION IS REQUIRED WHEN CONSTRUCTION ACTIVITY ENCRONES ON THE CRITICAL ROOT ZONE OF A TREE.
- SEE COLUMBUS TREE TECHNICAL MANUAL FOR ADDITIONAL TREE PROTECTION REQUIREMENTS.




01 TREE PROTECTION
NTS

SECTION

GENERAL NOTES:

- REMOVE DEAD AND BROKEN BRANCHES AND ALL SUCKER GROWTH. DO NOT DAMAGE OR REMOVE CENTRAL LEADER.
- THE TYPE OF TREES TO BE USED SHALL BE SELECTED FROM AN APPROVED LIST PROVIDED BY THE CITY, REFERENCE TREE MANUAL.
- SEE SCD 2179 BACKFILL WITHIN THE RIGHT-OF-WAY.




02 TREE PLANTING
NTS

SECTION

GENERAL NOTES:

- TREE SPACING AND MINIMUM TREE LAWN WIDTHS ALONG WITH THE TYPES OF TREES ACCEPTABLE FOR TREE LAWNS CAN BE FOUND IN THE TREE TECHNICAL MANUAL AND SHOWN IN THE TREE PLAN.




03 TREE LAWN
NTS

SECTION

GENERAL NOTES:

- FOR GROUPS OF TREES, PLACE BARRICADES AT THE TREE PROTECTION ZONE AROUND THE GROUPS PERIMETER.
- INSTALLATION OF TREE PROTECTION BARRICADES SHALL BE PERFORMED BEFORE ANY SITE DEVELOPMENT OR SITE DEMOLITION ACTIVITY TAKES PLACE.
- THE TREE PROTECTION BARRICADES SHALL REMAIN IN PLACE THROUGHOUT THE CONSTRUCTION PHASE AND UNTIL ALL SITE DEVELOPMENT ACTIVITIES ARE FULLY COMPLETE. ALL TREE PROTECTION FENCING AND WOOD CHIP MULCH SHALL BE REMOVED AT THE COMPLETION OF THE PROJECT. ANY REMOVAL OF CHIPS MUST BE DONE BY HAND.
- ANY DAMAGE THAT MAY OCCUR TO THE BARRICADES SHALL BE REPAIRED OR REPLACED TO THE ORIGINAL SPECIFICATIONS WITHIN 24 HOURS OF THE DAMAGE OCCURRING.
- THE AREA WITHIN THE TREE PROTECTION BARRICADES SHALL NOT BE USED FOR THE STORAGE OF ANY MATERIALS, SUPPLIES OR DEBRIS OR THE DISPOSAL OF ANY SOLID, LIQUID OR GASEOUS MATERIALS THAT COULD CAUSE HARM TO THE TREES.
- PUBLIC TREES THAT ARE DAMAGED DUE TO IMPROPER OR INSUFFICIENT TREE PROTECTION ARE WARRANTED FOR 1 YEAR POST-CONSTRUCTION AND ARE SUBJECT TO TREE MITIGATION. MONETARY TREE VALUE SHALL BE DETERMINED BY USING THE GUIDE FOR PLANT APPRAISAL, PUBLISHED BY THE INTERNATIONAL SOCIETY OF THE ARBORICULTURE OR OTHER SOURCES AS DETERMINED BY THE CITY FORESTER.
- BARRICADES ARE REQUIRED TO BE IN PLACE AROUND ALL TREES TO REMAIN BEFORE CONSTRUCTION ACTIVITIES COMMENCE.
- ANY PROPOSED UNDERGROUND UTILITIES SHALL BE ROUTED AROUND PROTECTED TREES TO THE OUTSIDE OF THE TREE'S DRIPLINE. IF THIS IS NOT FEASIBLE, AS DETERMINED BY THE COUNTY, A SLEEVE MAY BE USED UNDER THE TREE, PROVIDED THAT ALL ACCEPTABLE HORTICULTURAL/ARBORICULTURAL PRACTICES ARE ADHERED TO. ANY WORK WITHIN THE TREE PROTECTION ZONE MUST BE APPROVED VIA A FORESTRY PERMIT.



04 CURBED PLANTER
NTS

SECTION

PUBLIC TREE PLAN #

PROJECT OWNER
COLUMBUS RECREATION AND PARKS DEPARTMENT
100 East Broad Street
Columbus, OH 43206

PROJECT ADDRESS
XXXXX
XXXXXX

SHEET TITLE
STANDARD DETAILS

SHEET NUMBER
L401